

U.S. Department of Labor

Mine Safety and Health Administration

MSHA's Small Mine Office—Serving the small mines in America



Week 49

Location: _____ Supervisor: _____

Date: _____

Time: _____

Duration: _____

1) Compressed Gas Cylinders

- ☐ Must be secured (chains or straps at upper third of cylinder) and safety cap installed
- ☐ Keep in upright position
- ☐ Ensure contents of cylinders are properly identified by label/stenciling
- ☐ Handle cylinders with care. When moving make sure safety cap is hand tightened.
- ☐ Do not roll or drop cylinders, or let them bump violently against each other
- ☐ Clear cylinder valves of dust and dirt before attaching proper regulators. Some regulators are only for specific gases and should not be interchanged. Do not force connection fittings and never tamper with safety devices in cylinder valves or regulators

2) Defective Tools

- ☐ Never Use defective tools
- ☐ Inspect the tools for defects before using them
- ☐ Discard defective tools

3) Power Tools

- ☐ Know the applications and limitations of your tools
- ☐ Don't use power tools in damp or wet conditions
- ☐ Power tools should be grounded or double insulated
- ☐ Never remove the ground pin

Attendees:

_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

Employees Comments: